

# Alpine

Item # P3T-60290 - P3T-60307 (18 colorways)



Impact



Chemical



Abrasion

## PHYSICAL PROPERTIES

|              |                                     |
|--------------|-------------------------------------|
| Width        | Trim to 48"                         |
| Packaging    | 15-yd rolls                         |
| Thickness    | 0.030                               |
| Backing      | Heavy Polyester/ Cotton knit        |
| Repeat       | N/A                                 |
| Installation | Reverse hang, Random match          |
| Fire Safety  | Class "A" rated ASTM E-84; NFPA 286 |



Impact

Impact Resistance

ASTM D- 5420-10

Gardner Method

Pattern      In-Lbs

Alpine      +100



Chemical

Chemical Resistance

ASTM D- D-1308

Spot test covered 3.1.1

Cleaning

ASTM F-793

SECTION 7.5

Staining Agents

Grape Juice

Mustard

Black Sharpie

Ink Pen

Betadine

Shoe Polish

Lipstick

Black Rubber

Brake Fluid

Spray Paint

Results: Each staining agent

above was wiped clean with at least one listed cleaning agent.



Abrasion

Abrasion Resistance

ASTM D- 4060-14

Taber Method

Test Spec

CS-10F wheel

500 gram load @200 cycles

Weight loss: 0.02%

## ENVIRONMENTAL & HEALTH

|  |  |
|--|--|
| Indoor Air                               | Meets California Section 01350                     |
| Fungal Resistant                         | ASTM G-21  |
| Bacterial Resistant                      | ASTM G-22  |
| HPD                                      | third-party certified                              |
| EPD                                      | third-party certified                              |
| NSF/ANSI 342                             | third-party certified, ask distributor for details |
| Recycled content                         |  |
| California Prop 65, no labeling required |  |
| Non-phthalate                            |  |

Results: No change in P3TEC surface from exposure to these agents.

Best stain removal results can be achieved by use of progressively strong, non-abrasive cleaners, and which can be supplemented by use of a soft bristle brush.

## OTHER

5 year warranty against manufacturing defects.

Accessories: Coordinating corner guards and Type II wallcovering (on selected colorways) available.

Installs with techniques similar to Type II vinyl wallcovering, including seaming with overlap and double-cut process.

See full installation instructions from distributor.

Sold in 15-yd coreless rolls, one per shipping box (approximately 42 lbs)