


Product Specifications


Details		Performance Advantages			
Width	Trims to 48"		Impact	Chemical	Abrasion
Packaging	15 yard rolls				
Backing	Heavy Polyester/ Cotton knit	P3TEC	24 – 100+ (See Table)	Fully Chemical Resistant	Highly Resistant
Fire Safety	ASTM E-84, Class “A” NFPA 286				
Environmental and Health		Type III Wallcovering	15	Stain Resistant	Varies
Indoor Air Quality	Meets California Section 01350				
Fungal Resistant	ASTM G-21	Rigid Sheet	22 – 100+	Stain Resistant	Highly Resistant
Bacterial Resistant	ASTM G-22				
Sustainability	NSF/ANSI 342, Third-party certified				
EPD	Third-party certified				
HPD	Third-party certified				

 Impact

Impact Resistance

ASTM D-5420-10
Gardner Method

Pattern	In-Lbs
In-Grained	60
Raffia Weave	60
Sahara Silk	100+
Simplicity	100+
Stellar	100+
Stellar Streak	100+
Tic-Tac-Texture	60
Tranquility	100+
Uplift	24

 Chemical


Chemical Resistance

ASTM D-1308
Spot test covered 3.1.1

Cleaning Agents

Tide w/H2O
Virex
Ammonia
Isopropyl Alcohol
Goof Off
Fantastik
Lysol
Hydrogen Peroxide
Bleach
Methyl Ethyl Ketone

Results: No change in P3TEC surface from exposure to these agents.

 Abrasion

Cleaning

ASTM F-793
Section 7.5

Staining Agents

Grape Juice
Mustard
Black Sharpie
Ink Pen
Betadine
Shoe Polish
Lipstick
Black Rubber
Brake Fluid
Spray Paint

Results: Each staining agent above was wiped clean with at least one listed cleaning agent.

Abrasion Resistance

ASTM D-4060-14
Taber Method

Test Specs

CS-10F wheel
500 gram load @200 cycles
Weight loss: 0.02%

Best stain removal results can be achieved by use of progressively strong, non-abrasive cleaners, and which can be supplemented by use of a soft bristle brush.

Type II Wallcovering

For adjacent wall surfaces needing less protection, you can specify yardage for most of the pattern/ color options of the P3TEC program in Type II, 20 oz quality. See individual pages for availability.



Uplift
Bone White P3T-60112