

Bevel

Item # P3T-60230 - P3T-60246 (17 colorways)



PHYSICAL PROPERTIES

Width	Trim to 48"
Packaging	15-yd rolls
Thickness	0.034
Backing	Heavy Polyester/ Cotton knit
Repeat	N/A
Installation	Reverse hang, Random match
Fire Safety	Class "A" rated ASTM E-84



Impact

Impact Resistance	ASTM D- 5420-10
Gardner Method	
Pattern	In-Lbs
Bevel	72



Chemical

Chemical Resistance	Cleaning	Abrasion Resistance
ASTM D-1308	ASTM F-793	ASTM D- 4060-14
Gardner Method	SECTION 7.5	Taber Method
Cleaning Agents	Staining Agents	Test Spec
Tide w/H2O	Grape Juice	CS-10F wheel
Virex	Mustard	500 gram load @200 cycles
Ammonia	Black Sharpie	Weight loss: 0.02%
Isopropyl Alcohol	Ink Pen	
Goof Off	Betadine	
Fantastik	Shoe Polish	
Lysol	Lipstick	
Hydrogen Peroxide	Black Rubber	
Bleach	Brake Fluid	
Methyl Ethyl Ketone	Spray Paint	
Results: No change in P3TEC surface from exposure to these agents.	Results: Each staining agent above was wiped clean with at least one listed cleaning agent.	
	Best stain removal results can be achieved by use of progressively strong, non-abrasive cleaners, and which can be supplemented by use of a soft bristle brush.	



Abrasion

ENVIRONMENTAL & HEALTH

Indoor Air	Meets California Section 01350
Fungal Resistant	ASTM G-21
Bacterial Resistant	ASTM G-22
HPD	third-party certified
EPD	third-party certified
NSF/ANSI 342	third-party certified, ask distributor for details
Recycled content	
California Prop 65, no labeling required	
Non-phthalate	

OTHER

5 year warranty against manufacturing defects.

Accessories: Coordinating corner guards and Type II wallcovering (on selected colorways) available.

Installs with techniques similar to Type II vinyl wallcovering, including seaming with overlap and double-cut process.

See full Installation Instructions from distributor.

Sold in 15-yd coreless rolls, one per shipping box (approximately 42 lbs)