

# Exhale

Item # P3T-60335 - P3T-60343 (6 colorways)



## PHYSICAL PROPERTIES

Width	Trim to 48"
Packaging	15-yd rolls
Thickness	0.032
Backing	Heavy Polyester/ Cotton knit
Repeat	N/A
Installation	Reverse hang, Random match
Fire Safety	Class "A" rated ASTM E-84



### Impact

Impact Resistance	ASTM D- 5420-10
Gardner Method	

Pattern	In-Lbs
Exhale	60



### Chemical

Cleaning Agents	Tide w/H2O
Virex	
Ammonia	
Isopropyl Alcohol	
Goof Off	

Fantastik	
Lysol	
Hydrogen Peroxide	
Bleach	
Methyl Ethyl Ketone	

Results: No change in P3TEC surface from exposure to these agents.

Best stain removal results can be achieved by use of progressively strong, non-abrasive cleaners, and which can be supplemented by use of a soft bristle brush.



### Abrasion

Abrasion Resistance	ASTM D- 4060-14
Test Spec	
CS-10F wheel	
500 gram load @200 cycles	
Weight loss: 0.02%	

## ENVIRONMENTAL & HEALTH

Indoor Air	Meets California Section 01350
Fungal Resistant	ASTM G-21
Bacterial Resistant	ASTM G-22
HPD	third-party classified
EPD	third-party certified
NSF/ANSI 342	third-party certified, ask distributor for details

Staining Agents	Grape Juice
Mustard	
Black Sharpie	
Ink Pen	
Betadine	

Results: Each staining agent above was wiped clean with at least one listed cleaning agent.

## OTHER

5 year warranty against manufacturing defects.

Accessories: Coordinating corner guards and Type II wallcovering (on selected colorways) available.

Installs with techniques similar to Type II vinyl wallcovering, including seaming with overlap and double-cut process.

See full Installation Instructions from distributor.

Sold in 15-yd coreless rolls, one per shipping box (approximately 42 lbs)