

South Beach Silk

Item # P3T-60425 - P3T-60439 (15 colorways)



Impact



Chemical



Abrasion

PHYSICAL PROPERTIES

Width	Trim to 48"
Packaging	15-yd rolls
Thickness	0.032
Backing	Heavy Polyester/ Cotton knit
Repeat	N/A
Installation	Reverse Random
Fire Safety	Class "A" rated ASTM E-84



Impact

Impact Resistance	ASTM D- 5420-10
Gardner Method	

Pattern	In-Lbs
South Beach Silk	60



Chemical

Chemical Resistance	Cleaning
ASTM D-1308	ASTM F-793
Gardner Method	SECTION 7.5
Pattern	Cleaning Agents
In-Lbs	Tide w/H2O
South Beach Silk	Virex
60	Ammonia
	Isopropyl Alcohol
	Goof Off
	Fantastik
	Lysol
	Hydrogen Peroxide
	Bleach
	Methyl Ethyl Ketone

Results: No change in P3TEC surface from exposure to these agents.

Staining Agents
Grape Juice
Mustard
Black Sharpie
Ink Pen
Betadine
Shoe Polish
Lipstick
Black Rubber
Brake Fluid
Spray Paint

Results: Each staining agent above was wiped clean with at least one listed cleaning agent.

Best stain removal results can be achieved by use of progressively strong, non-abrasive cleaners, and which can be supplemented by use of a soft bristle brush.

OTHER

5 year warranty against manufacturing defects.

Accessories: Coordinating corner guards and Type II wallcovering (on selected colorways) available.

Installs with techniques similar to Type II vinyl wallcovering, including seaming with overlap and double-cut process.

See full Installation Instructions from distributor.

Sold in 15-yd coreless rolls, one per shipping box (approximately 42 lbs)