

Tranquility

Item # P3T-60025 - P3T-60042 (18 colorways)



Impact



Chemical



Abrasion

PHYSICAL PROPERTIES

Width	Trim to 48"
Packaging	15-yd rolls
Thickness	0.032
Backing	Heavy Polyester/ Cotton knit
Repeat	N/A
Installation	Reverse hang, Random match
Fire Safety	Class "A" rated ASTM E-84



Impact

Impact Resistance	ASTM D- 5420-10
Gardner Method	
Pattern	In-Lbs
Tranquility	60



Chemical

Chemical Resistance	Cleaning
ASTM D-1308	ASTM F-793
Spot test covered 3:1:1	SECTION 7.5
Cleaning Agents	Staining Agents
Tide w/H2O	Grape Juice
Virex	Mustard
Ammonia	Black Sharpie
Isopropyl Alcohol	Ink Pen
Goof Off	Betadine
Fantastik	Shoe Polish
Lysol	Lipstick
Hydrogen Peroxide	Black Rubber
Bleach	Brake Fluid
Methyl Ethyl Ketone	Spray Paint

Results: No change in P3TEC surface from exposure to these agents.

Results: Each staining agent above was wiped clean with at least one listed cleaning agent.
Best stain removal results can be achieved by use of progressively strong, non-abrasive cleaners, and which can be supplemented by use of a soft bristle brush.



Abrasion

ENVIRONMENTAL & HEALTH

Indoor Air	Meets California Section 01350
Fungal Resistant	ASTM G-21
Bacterial Resistant	ASTM G-22
HPD	third-party certified
EPD	third-party certified
NSF/ANSI 342	third-party certified, ask distributor for details
Recycled content	
California Prop 65, no labeling required	
Non-phthalate	

OTHER

5 year warranty against manufacturing defects.

Accessories: Coordinating corner guards and Type II wallcovering (on selected colorways) available.

Installs with techniques similar to Type II vinyl wallcovering, including seaming with overlap and double-cut process.

See full Installation Instructions from distributor.

Sold in 15-yd coreless rolls, one per shipping box (approximately 42 lbs)