

Cement

Item # P3T-60325 - P3T-60332 (8 colorways)



PHYSICAL PROPERTIES

Width	Trim to 48"
Packaging	15-yd rolls
Thickness	0.034
Backing	Heavy Polyester/ Cotton knit
Repeat	N/A
Installation	Reverse hang, Random match
Fire Safety	Class "A" rated ASTM E-84



Impact

Impact Resistance	ASTM D- 5420-10
	Gardner Method
Pattern	In-Lbs
Cement	88



Chemical

Chemical Resistance	ASTM D- D-1308
	Spot test covered 3.1.1
Cleaning Agents	
Tide w/H2O	
Virex	
Ammonia	
Isopropyl Alcohol	
Goof Off	
Fantastik	
Lysol	
Hydrogen Peroxide	
Bleach	
Methyl Ethyl Ketone	



Abrasion

Abrasion Resistance	ASTM D- 4060-14
	Taber Method
Test Spec	
CS-10F wheel	
500 gram load @200 cycles	
Weight loss: 0.02%	

ENVIRONMENTAL & HEALTH

Indoor Air	Meets California Section 01350
Fungal Resistant	ASTM G-21
Bacterial Resistant	ASTM G-22
HPD	third-party certified
EPD	third-party certified
NSF/ANSI 342	third-party certified, ask distributor for details
Recycled content	
California Prop 65, no labeling required	
Non-phthalate	

Results: No change in P3TEC surface from exposure to these agents.

Best stain removal results can be achieved by use of progressively strong, non-abrasive cleaners, and which can be supplemented by use of a soft bristle brush.

Results: Each staining agent above was wiped clean with at least one listed cleaning agent.

OTHER

5 year warranty against manufacturing defects.

Accessories: Coordinating corner guards and Type II wallcovering (on selected colorways) available.

Installs with techniques similiar to Type II vinyl wallcovering, including seaming with overlap and double-cut process.

See full installation instructions from distributor.

Sold in 15-yd coreless rolls, one per shipping box (approximately 42 lbs)