

# Exhale

Item # P3T-60335 - P3T-60343 (6 colorways)



Impact



Chemical



Abrasion

## PHYSICAL PROPERTIES

|              |                              |
|--------------|------------------------------|
| Width        | Trim to 48"                  |
| Packaging    | 15-yd rolls                  |
| Thickness    | 0.032                        |
| Backing      | Heavy Polyester/ Cotton knit |
| Repeat       | N/A                          |
| Installation | Straight Random              |
| Fire Safety  | Class "A" rated ASTM E-84    |



Impact

Impact Resistance

ASTM D- 5420-10

Gardner Method

Pattern

Exhale

In-Lbs



Chemical

Chemical Resistance

ASTM D-1308

Spot test covered 3:1:1

Cleaning

ASTM F-793

SECTION 7.5



Abrasion

Abrasion Resistance

ASTM D- 4060-14

Taber Method

## ENVIRONMENTAL & HEALTH

|                     |  |
|---------------------|--|
| Indoor Air          | Meets California Section 01350                     |
| Fungal Resistant    | ASTM G-21  |
| Bacterial Resistant | ASTM G-22  |
| HPD                 | third-party classified                             |
| EPD                 | third-party certified                              |
| NSF/ANSI 342        | third-party certified, ask distributor for details |

Cleaning Agents

Tide w/H2O

Virex

Ammonia

Isopropyl Alcohol

Goof Off

Fantastik

Lysol

Hydrogen Peroxide

Bleach

Methyl Ethyl Ketone

Staining Agents

Grape Juice

Mustard

Black Sharpie

Ink Pen

Betadine

Shoe Polish

Lipstick

Black Rubber

Brake Fluid

Spray Paint

Results: No change in P3TEC surface from exposure to these agents.

Results: Each staining agent above was wiped clean with at least one listed cleaning agent.

Best stain removal results can be achieved by use of progressively strong, non-abrasive cleaners, and which can be supplemented by use of a soft bristle brush.

## OTHER

5 year warranty against manufacturing defects.

Accessories: Coordinating corner guards and Type II wallcovering (on selected colorways) available.

Installs with techniques similar to Type II vinyl wallcovering, including seaming with overlap and double-cut process.

See full Installation Instructions from distributor.

Sold in 15-yd coreless rolls, one per shipping box (approximately 42 lbs)